



Russia QTZ100 Tower Crane City Building Constructon PT6013 Crane Tower L46 Mast

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM TOWER CRANE
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTP6013 Flattop Tower Crane
- Minimum Order Quantity: 1
- Price: \$88500-99500 per set
- Packaging Details: Naked packing, 6*40'HC containers Per set
PT6013 Topless tower crane
- Delivery Time: 20 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 30 sets per month



Product Specification

- Application: Buildings And Projects
- Type: Fixing Hydraulic Climbing
- Load: 8tons
- Working Jib: 60m
- Free Height: 50m-60m
- Mast section: 1.6*3M L46
- Main Chord: 180*18mm Angle Steel
- Color: Yellow Or Others
- Highlight: **Russia QTZ100 tower crane, construction PT6013 crane tower, flat top tower crane L46 mast**



More Images



Product Description

Russia QTZ100 Tower Crane City Building Constructon PT6013 Crane Tower L46 Mast

Short parameters

1. QTZ100(PT6013) Flat Top Tower Crane
2. Type: fixed and external climbing
3. jib length: 60m
4. tip load: 1.3t
5. max. load: 10t
6. freestanding height: 45m

Specification

Rated Lifting Moment	1000KN.m
Rated Loading Capacity	8t
Max. Lifting Load	8t
Tip Load	1.3t
Max. Lifting Height	150m
Span	60m
Free standing height	45m
Rope length	400m
Working range	3-60m
Slewing speed	0.6r/min
Trolley speed	40/20 m/min
Jacking-up speed	0.4 m/min
Hoisting speed(m/min)	(a=2)0-80 (a=4)0-40 control with inverter
Power supply	380V/50Hz or according to client's requirements
Power Capacity	46.2kw
Electric switch box	Schneider
Main materials	135*12mm / 180*10mm
Mast section dimensions	1.835*1.835*2.5 m or 1.6*1.6*3m or others

Our advantage

1. 15 years of experience in supplying new external climbing tower crane with HYCM Brand.
2. Export to more than 20 countries with CE/ISO/GOST/CU-TR Certificates.
3. Stationary/Traveling and internal climbing type tower crane are available
4. Impeller blasting/rust protection paint
5. Advanced painting process
6. Strict and experience welding line
7. New designed mast, can be used to Internal and external climbing tower crane
8. Well known brand mechanism system, Schneider Electronic control system, Jjiangte and Jiuhe motor
9. Engineers available to service machinery overseas.
10. For warranty, it is 12 months from the B/L date. What's more, some free easy worn spare parts are provided together with the crane.

Why choose us

1. A professional tower crane supplier in China with 15 years experience
2. Exported to more than 20 countries with ISO9001 & CE & GOST Certifications
3. Hydraulic self-climbing mechanism
4. Variable-frequency slewing mechanism
5. Variable-speed frequency PLC control System
6. Operation data display screen and Safety monitoring system (Black Box)
7. Various safety devices

Components

Mast: the main supporting tower of the crane. It is made of steel trussed sections that are connected together during installation.

Operating cabin: the operating cabin sits just above the slewing unit. It contains the operating controls.

Jib: the jib, or operating arm, extends horizontally from the crane. A "luffing" jib is able to move up and down; a fixed jib has a rolling trolley that runs along the underside to move goods horizontally.

Hook: the hook (or hooks) is used to connect the material to the crane. It hangs at the end of thick steel cables that run along the jib to the motor.

Weights: Large concrete counterweights are mounted toward the rear of the mast, to compensate for the weight of the goods lifted.

Safety Device

1. 3 obstacle lights
2. Height limiter
3. Slewing limiter
4. Range/ trolley limiter
5. Weight limiter
6. Moment limiter
7. Anemometer
8. Block box(optional)

Photos



More products available: Construction Machinery

Tower Cranes

- QTZ Topkit/Hammer Head Tower Cranes: Working jib from 30-75m and max.load from 4-25t.
- PT Topless/Flat Top Tower Cranes: Working jib from 30-80m and max.load from 4-32t.
- D Luffing Tower Crane: Working jib from 25-60m and max.load from 3-25t.
- QD Derrick Crane: load from 3t to 25t for disassemble inner climbing tower cranes.

□

SC Construction Man and Material Elevator

- Rack and pinion elevator, special for the lifting work of construction Man and Material, 1000kg to 4000kg capacity, Passenger and Material, up to 200m. .

□

SS Building Material Lift / Hoist

- Wire rope lift, special material lifting work in construction site, 1000kg to 2000kg capacity, no passenger, up to 60m.



SJY Scissor Lift



Gantry Crane



Double Beam Bridge Crane



Single Beam Bridge Crane



Half gantry crane



Double Girder gantry crane

Our advantage

1. Choose high-quality materials
2. One-stop customized service
3. Professional after-sales team



Rubber tyred gantry crane



Electric Hoist



Jib Crane



Electric Winch

Small Jib Crane



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China